

### UHF Wireless Meeting System

With high flexibility and reliability, our UHF wireless meeting microphone system is an ideal choice for mobile conference systems. It offers simple operation, compact structures. The wireless meeting microphone system can be perfectly integrated into any meeting rooms, without additional wiring. In addition, multiple devices can be used together.

#### Wireless Meeting System HT-280U

- ◆ System include 1 receiver and 2 transmitter microphone
- ◆ Operating frequency: 740-790MHz
- ◆ Adopt CPU control with PLL combined technology
- ◆ Frequency selection of IR
- ◆ Frequency stability:  $< \pm 30\text{PPm}$
- ◆ With FM Max frequency adjusting:  $\pm 45\text{KHz}$
- ◆ Pre-warning display for weak battery
- ◆ Audio frequency response compression and auto electricity level control circuit



**HT-280U**

#### Wireless Meeting System HT-860

- ◆ System include 1 receiver and 4 transmitter microphone
- ◆ Operating frequency: 550-980MHz
- ◆ Adopt CPU control with PLL combined technology
- ◆ Frequency selection of IR
- ◆ Frequency stability:  $< \pm 30\text{PPm}$
- ◆ With FM Max frequency adjusting:  $\pm 45\text{KHz}$
- ◆ Pre-warning display for weak battery
- ◆ Audio frequency response compression and auto electricity level control circuit



**HT-860**

#### Wireless Meeting System HT-860

- ◆ System include 1 receiver and 8 transmitter microphone
- ◆ Operating frequency: 550-980MHz
- ◆ Frequency response: 40Hz-18KHz
- ◆ Dynamic range:  $> 105\text{dB}$
- ◆ T.H.D:  $< 0.5\%$
- ◆ Adopt CPU control with PLL combined technology
- ◆ Frequency selection of IR
- ◆ Frequency stability:  $< \pm 30\text{PPm}$
- ◆ With FM Max frequency adjusting:  $\pm 45\text{KHz}$
- ◆ Pre-warning display for weak battery
- ◆ Audio frequency response compression and auto electricity level control circuit
- ◆ Audio output: Balance: 0-600mV, unbalance: 0-300mV



**HT-1188**